

Measurement and Evaluation of Reliability, Availability and Maintainability of a Diesel Locomotive Engine

D.Bose¹, G.Ghosh², K.Mandal³, S.P.Sau⁴, S.Kunar⁵

^{1, 2, 3}Mechanical Engineering & ⁴Computer Science and Technology, NITTTR, India
⁵Production Engineering, Jadavpur University, India

Abstract- The growing complexity of equipments and systems often lead to failures and as a consequence the aspects of reliability, maintainability and availability have come into forefront. The failure of machineries and equipments causes disruption in production resulting from a loss of availability of the system and also increases the cost of maintenance. The present study deals with the determination of reliability and availability aspects of one of the significant constituent in a Railway Diesel Locomotive Engine. In order to assess the availability performance of these components, a broad set of studies has been carried out to gather accurate information at the level of detail considered suitable to meet the availability analysis target. The Reliability analysis is performed using the Weibull Distribution and the various data plots as well as failure rate information help in achieving results that may be utilized in the near future by the Railway Locomotive Engines for reducing the unexpected breakdowns and will enhance the reliability and availability of the Engine. In this work, ABC analysis has been used for the maintenance of spare parts inventory. Here, compressor and vehicle and structures are used to focus on the reliability, maintainability and availability aspects.

Index Terms- Availability, ABC analysis, compressor, maintainability, reliability, vehicle and structures, Weibull Distribution.

I. INTRODUCTION

The Reliability of an item is the probability that the item will perform a specific function under specified operational and environmental conditions at end throughout a specified time [1]. Reliability must have certain criteria. It depends on numerous factors, most of which are random. It is difficult to measure reliability since there is no instrument by means of which this may be done for particular equipment. The respective reliabilities of the various components of complex equipment depend on the technology of their production, the quality of materials used in their manufacture, the conditions or environment in which they operate and so on. In view of these considerations, the reliability of equipment is closely related to several uncertainty factors. The Quantitative study of uncertainty, therefore, forms the starting point for a quantitative analysis of reliability. The theory which deals with the study of uncertainty is the probability theory. The maintenance policy will cover issues regarding general repairs, repair or discard policies, emergency recorder policies, inventory control, provisioning of spares, etc. It is possible to define some of the maintenance policies in advance and take design decision accordingly. The process of designing involves decision regarding module size, test procedures, built-in-redundancies, and degree of automation, inspection intervals, special test equipment, and safety requirements and so on. Availability is a performance criterion for repairable systems that accounts for both the reliability and maintainability properties of a component or system. ABC analysis helps segregating the item from one another and tells how much valued the item is and controlling it to what extent is in the interest of the organization [2].

II. RAILWAY DIESEL LOCOMOTIVE ENGINE AND ITS COMPONENTS

The following fig 1 shows a Railway Diesel Locomotive Engine. The engine is of 'V' design, and is manufactured in 16 cylinders. The cylinders are arranged into pairs of cylinders, each pair using a common throw on the crankshaft. The cylinders are divided into two banks, left and right.



Figure1: Railway Diesel Locomotive Engine.

A Railway Diesel Locomotive Engine has the following main sub-systems.

1. Compressor
2. Vehicle and structures

III. FAILURE

Failure is any event that impacts a system in a way that adversely affects the system criteria. For example, the criteria could include output in a sold-out condition, or maintenance cost or capital resources in a constrained budget cycle, environmental excursions or safety, etc. A failure definition should contain specific criteria and not be ambiguous. Failure definition can change on a given system over time.

Field failures do not generally occur at a uniform rate, but follow a distribution in time commonly describe as a "bathtub curve." The life of a device can be divided into three regions: Infant Mortality Period, where the failure rate progressively improves; Useful Life Period, where the failure rate remains constant; and Wear out Period, where failure rates begin to increase. Within a population of units is a small sub-group of units with latent defects that will fail when exposed to a stress that would otherwise be benign to a good unit. With the failure of the weak units, the remaining population is more reliable, and the failure rate is known to decrease. Units that pass the Infant Mortality Period have a high probability of surviving the conditions provided by the system and its environment. Failures that occur during the Useful Life Period are residual defects surviving Infant Mortality, unpredictable system or environmental conditions, or premature wear out.




Figure 2: Bath-tub curve describing failure rates at different periods of life

3.1 Reliability Prediction

A reliability prediction is simply the analysis of parts and components which effort to predict and calculate the rate at which an item will fail. A reliability prediction is one of the most common forms of reliability analyses for calculating failure rate and MTBF, MTTR, Availability etc [3].

3.1.1 Mean Time to Failure (MTTF)

It is the expected value of time t or the mean of the TTF (Time to Failure) distribution when one item is put into operation [4]

When and only when failure rate is a constant or $\lambda = \lambda(t)$ then

$$MTTF = \int_0^{\infty} R(t) dt = \int_0^{\infty} e^{-\lambda t} dt = \frac{1}{\lambda} \quad \text{--- (3.1)}$$

3.1.2 Mean Time between Failures (MTBF)

It is the expected average time between failure events that cause the item to go down. Therefore MTBF can be defined as the average time (generally expressed in hours) that a component works without failure If and only if the item has constant failure rate then,

$$MTBF = \int_0^{\infty} R(t) dt = \frac{1}{\lambda} \quad \text{--- (3.2)}$$

3.2 Failure Distribution

The goal of system modeling is to provide quantitative forecasts of various system performance measures such as downtime, availability, and number of failures, capacity, and cost. Evaluation of these measures is important to make optimal decisions when designing a system to either minimize overall cost or maximize a system performance measure within the allowable budget and other performance-based constraints.

Two important factors taken into account in the analysis of a system are the failure and repair behaviors of the system components. The failure and repair rates of components are often defined in terms of distributions, or how the failures and repairs occur during the time period the system is operational. Therefore, selecting the appropriate distributions for these failure and repair times is critical to analyze system metrics accurately.

A useful way to easily visualize the characteristics of a failure or repair distribution is through the use of Probability Density Functions (PDF) [5]. In general, the shape or type of failure distribution depends upon the component's failure mechanisms. Similarly, the shape or type of repair distribution depends upon several factors associated with component repairs. Several methods are used to determine the distribution that best fits a given failure or repair pattern. Or, if failures or repairs are known to follow a particular distribution, the specific parameters that define this pattern can be determined by using the known failure and repair times.

If the type of distribution is not known in advance, then the distribution that best fits the failure or repair times can be found using statistical methods. To find the best distribution manually, probability plot papers are used. Alternatively, engineering software products can also be used to generate probability plots and determine best-fit distributions. In general, it is better to use available software tools because best-fit distributions are determined using scientific analysis rather than human judgment, which must be used when manually creating probability plots. Such engineering software products are commonly referred to as "Weibull" analysis tools, simply because Weibull is a widely accepted, commonly used distribution for describing failure and repair rates.

Determining the failure and repair distributions of a system and its components is a significant part of evaluating the reliability of the design. Distributions may be referred to as single-parameter or two-parameter distributions. For single-parameter distributions, only one variable is used to define the shape of the curve. Two-parameter distributions require two variables to accurately model the distribution.

3.3 Collection of Data

The most essential precondition for reliability and failure analysis or maintenance planning is the availability of relevant data. For the present analysis, data related to Railway Diesel Locomotive Engine, its Mechanical system and Electrical system failures during last five years [2007 January to 2011 December] are collected. The database includes no. of breakdowns related to different types of systems or components failures of Diesel Locomotive Engine and their monthly or year wise available No. of failure of a component or system, cause of failure and corrective action taken previously.

The documentation of failure data (table 1 and fig.3) on Diesel Locomotive Engine, daily breakdown record has been collected from the daily maintenance statistics lab in the DEISEL SHED.

Table 1:No. of Failures of different components

Sl. No.	Name of Different Components	No. of Failures
1	Compressor	04
2	Vehicle and structures	05




Figure 3:No. of Failures of different components

3.4 Failures of Compressor/Exhauster/ Brake system

In analyzing the various causes of failure in Compressor/Exhauster and Brake system it has been noticed in Fig.4 that the expresser 1st coupling gasket damaged as well as air leakage from expresser side cover gasket each comprises the 50% of the total failure.




Figure 4: Failures of Compressor

3.5 Failures of vehicle and structures

The various failure components of vehicle and structures are illustrated in figure3 wherein trolley side bearer rubber loading pad displaced damage and Brake rigging damage equally contribute.




Figure 5: Failures of vehicle and structures

IV. RELIABILITY ANALYSIS

The Locomotive Engine under investigation is composed three components. The components are compressor, vehicle and structures.

4.1 Hazard Model & Probability Distribution

The initial stage of reliability analysis is to predict the hazard model of the failures and to choose a distribution among various probability distributions like Normal distribution, Exponential distribution, Poisson distribution, Weibull distribution etc. The probability distributions are grouped as follows:

- Hazard model with constant failure rate can be followed by normal, exponential distributions.
- Hazard model with increasing or decreasing failure rates can be followed by Weibull distribution.

4.2 Graphical Evaluation for Reliability Prediction

There are generally two ways for graphical evaluation visualizes -Exponential plot and Weibull Plot. When the failure rate is constant, the distribution follows exponential probability law and when failure rate is not constant i.e. non-linear hazard model follows Weibull distribution.

4.3 Linear Regression Analysis: Selection of Distribution

The observed data regarding the failures of different components of the Railway Diesel Locomotive Engine shows that the failure rates of the components are not constant. So the Weibull distribution model can be adopted. Moreover the technique of linear regression analysis confirms the suitability to use Weibull distribution for the different components of the Railway Diesel Locomotive Engine. The analysis determines the best-fit line in the least square sense. The least square test has been performed to obtain the increasing/decreasing rate of failures [6].

Linear regression analysis has been carried out by using the Probability equation.

$$R_{x, f(x)} = \frac{\sum [x f(x)] - \frac{(\sum x)(\sum f(x))}{N}}{\sqrt{[\sum (x^2) - \frac{(\sum x)^2}{N}] [\sum f(x)^2 - \frac{(\sum f(x))^2}{N}]}} \quad (4.1)$$

Where,

x = Breakdown hours

Y = f(x) = Cumulative % failures

N = number of trials

$R_{x, f(x)}$ = Correlation coefficient

Failure data of the different components of the Diesel Locomotive Engine is used for determining the correlation co-efficient (Table 2). From the concept of probability, we know that the correlation coefficient must be in between -1.0 to +1.0. If the correlation coefficient is positive, then the failure rate is increasing, otherwise the rate is decreasing. The correlation coefficients of the different components of the Railway Diesel Locomotive Engine under study shows increasing rate of failures. Weibull distribution can be applied for the estimation of reliability of the different components of the Railway Diesel Locomotive Engine.

Table 2: Correlation Coefficient

Name of Components	Correlation Coefficient
Compressor	0.783
Vehicle and Structures	0.741

4.4 Weibull Distribution

About all the distributions available for reliability calculations, the Weibull distribution [7] is the only unique to the field. Allodia Weibull (1887-1979) pointed out that normal distributions are not applicable for characterizing initial metallurgical strengths during his study on metallurgical failures. He then introduced a function that could embrace a great variety of distributions and used seven different case studies to demonstrate how this function allowed the data to select the most appropriate distribution from a broad family of Weibull distributions. Probably the most widely used distribution in reliability engineering, the Weibull distribution can model failures caused by fatigue, corrosion, mechanical abrasion, diffusion and other degradation processes.

The two parameter Weibull distribution requires characteristic life (η) and shape factor (β) values. Beta (β) determines the shape of the distribution. If β is greater than 1, the failure rate is increasing. If β is less than 1, the failure rate is decreasing. If β is equal to 1, the failure rate is constant. There are several ways to check whether data follows a Weibull distribution, the best choice is to use a Weibull analysis software product. If such a tool is not available, data can be manually plotted on a Weibull probability plot to determine if it follows a straight line. A straight line on the probability plot indicates that the data is following a Weibull distribution.




Figure 6: Weibull Distribution

Reliability analysis of the selected components of the Railway Locomotive Engine has been carried out with due consideration of failure as an indication of the underlying cause of failure has been summarized in term of Weibull shape parameter. Weibull shape parameter β also indicates whether the failure rate is constant or increasing or decreasing if $\beta = 1.0$, $\beta > 1.0$, $\beta < 1.0$ respectively. The cumulative % failures versus operating time data are plotted on Weibull graph [Fig.12 & 13] and the values of the parameters are obtained using the statistical software 'MINITAB15'.

Table 3: Weibull plot for Compressor

Sl. No	Month	Monthly Operating Time(Hours)	No of Failures	Percentage Failures	Cumulative % Failures
1	January'07	720	0	0	0
2		620	0	0	0
3		576	0	0	0
4		600	0	0	0
5		708	0	0	0
6		700	1	25	25
7		734	0	0	25
8		734	0	0	25
9		648	0	0	25
10		734	0	0	25
11		672	0	0	25
12		670	1	25	50
13	January'08	724	0	0	50
14		686	0	0	50
15		732	0	0	50
16		638	0	0	50
17		734	0	0	50
18		710	0	0	50
19		660	0	0	50
20		710	0	0	50
21		708	0	0	50
22		744	0	0	50

23		624	0	0	50
24		734	0	0	50
25	January'09	696	0	0	50
26		600	0	0	50
27		733	0	0	50
28		708	0	0	50
29		720	0	0	50
30		696	0	0	50
31		734	0	0	50
32		718	0	0	50
33		710	0	0	50
34		672	0	0	50
35		710	1	25	75
36		744	0	0	75
37	January'10	600	0	0	75
38		600	0	0	75
39		720	0	0	75
40		576	0	0	75
41		744	0	0	75
42		696	0	0	75
43		600	0	0	75
44		720	0	0	75
45		720	0	0	75
46		696	0	0	75
47		672	0	0	75
48		734	0	0	75
49	January'11	732	0	0	75
50		576	0	0	75
51		144	0	0	75
52		552	1	25	100
53		504	0	0	100
54		648	0	0	100
55		720	0	0	100
56		696	0	0	100
57		600	0	0	100
58		600	0	0	100
59		648	0	0	100
60		732	0	0	100

Table 4: Weibull plot for Vehicle and structures

SL. NO	Month	Monthly Operating Time(Hours)	No of Failures	Percentage Failures	Cumulative % Failures
1	January'07	720	0	0	0
2		620	0	0	0
3		576	0	0	0
4		600	0	0	0
5		708	0	0	0

6		700	1	20	20
7		734	0	0	20
8		734	0	0	20
9		648	0	0	20
10		734	0	0	20
11		672	0	0	20
12		670	0	0	20
13	January'08	724	0	0	20
14		686	0	0	20
15		732	0	0	20
16		638	0	0	20
17		734	1	20	40
18		710	1	20	60
19		660	0	0	60
20		710	0	0	60
21		708	0	0	60
22		744	0	0	60
23		624	0	0	60
24		734	0	0	60
25	January'09	696	0	0	60
26		600	0	0	60
27		733	0	0	60
28		708	0	0	60
29		720	0	0	60
30		696	0	0	60
31		734	0	0	60
32		718	0	0	60
33		710	0	0	60
34		672	1	20	80
35		710	0	0	80
36		744	0	0	80
37	January'10	600	0	0	80
38		600	0	0	80
39		720	0	0	80
40		576	0	0	80
41		744	0	0	80
42		696	0	0	80
43		600	0	0	80
44		720	0	0	80
45		720	0	0	80
46		696	0	0	80
47		672	0	0	80
48		734	0	0	80
49	January'11	732	0	0	80
50		576	0	0	80
51		144	0	0	80
52		552	1	20	100

53		504	0	0	100
54		648	0	0	100
55		720	0	0	100
56		696	0	0	100
57		600	0	0	100
58		600	0	0	100
59		648	0	0	100
60		732	0	0	100




Figure7: Weibull plot for compressor




Figure 8: Weibull plot for vehicle and structure

V. AVAILABILITY ANALYSIS

Availability is a performance criterion for repairable system or any normal system that accounts for both the reliability and maintainability properties of a component of a system is operating properly when it is required to use. As a matter of fact availability is the probability that a system is not failed or undergoing a repair action / maintenance job when it needs to be used. So the estimation

of availability plays vital role of both reliability and maintainability aspects are considered for a system or components under investigation.

5.1 Availability

Availability is a performance criterion for repairable systems that accounts for both the reliability and maintainability properties of a component or system. It is defined as the probability that the system is operating properly when it is requested for use. That is availability is the probability that a system is not failed or undergoing repair action when it needs to be used [2].

$$A_{IN} = MTBF / (MTBF + MTTR) \quad \text{--- (5.1)}$$

It is possible to define three types of availability depending on the time elements we consider.

5.1.1 Inherent Availability

This is a probability that a system or equipment shall operate satisfactorily when used under stated conditions in an ideal support environment, without consideration for any scheduled or preventive maintenance at any given time. Mathematically it is expressed [2] as

$$A_{IN} = MTBF / (MTBF + MTTR) \quad \text{--- (5.2)}$$

5.1.2 Achieved Availability

This is a probability that a system or equipment shall operate satisfactorily when used under stated conditions in an ideal support environment at any given time. It may be expressed as [2]

$$A_a = MTBM / (MTBM + MDT) \quad \text{--- (5.3)}$$

Where, MTBM is the mean active-maintenance down time resulting from both preventive and corrective maintenance.

5.1.3 Operational Availability

In any real operation, we cannot reduce administrative down time and supply downtime to zero. A certain amount of delay will always be caused by time elements such as these and if they are taken into account then we obtain the operational availability. It may be defined as the probability that a system or equipment shall operate satisfactorily when used under stated conditions and in an actual supply environment at any given time. It may be expressed [2] as

$$A_{OP} = MTBF / (MTBF + MDT) \quad \text{--- (5.4)}$$

In general the availability of a system is a complex function of reliability maintainability and supply effectiveness. This can be expressed as

$$A_s = f(R_s, M_s, S_s) \quad \text{--- (5.5)}$$

Where, A_s = System Availability, S_s = Supply Effectiveness, R_s = System Reliability, M_s = System Maintainability.

Table 5: Estimation of availability of Compressor

Sl. No	Month	Uptime (hours)	Downtime (hours)	No. of failures	MTBF (hour)	Hazard rate	MDT (hours)	A_{OP}	MTTR (hours)	A_{IN}
1	January'07	720	24	0	***	0	***	1	0	1
2		620	12	0	***	0	***	1	0	1
3		576	144	0	***	0	***	1	0	1
4		600	120	0	***	0	***	1	0	1
5		708	36	0	***	0	***	1	0	1
6		700	20	1	700	0.0011	26	0.964	7.8	0.988
7		734	10	0	0	0	***	1	0	1
8		734	10	0	0	0	***	1	0	1
9		648	72	0	0	0	***	1	0	1
10		734	10	0	0	0	***	1	0	1
11		672	48	0	0	0	***	1	0	1
12		670	24	1	0		744	1	223.2	1
13	January'08	724	10	0	0	0	***	1	0	1
14		686	10	0	0	0	***	1	0	1
15		732	12	0	0	0	***	1	0	1
16		638	82	0	0	0	***	1	0	1
17		734	10	0	0	0	***	1	0	1

18		710	10	0	0	0	***	1	0	1
19		660	84	0	0	0	***	1	0	1
20		710	10	0	0	0	***	1	0	1
21		708	12	0	0	0	***	1	0	1
22		744	0	0	0	0	***	1	0	1
23		624	72	0	0	0		1	0	1
24		734	10	0	0	0		1	0	1
25	January'09	696	48	0	0	0		1	0	1
26		600	72	0	0	0		1	0	1
27		733	10	0	0	0		1	0	1
28		708	12	0	0	0		1	0	1
29		720	0	0	0	0		1	0	1
30		696	24	0	0	0		1	0	1
31		734	10	0	0	0		1	0	1
32		718	26	0	0	0		1	0	1
33		710	10	0	0	0		1	0	1
34		672	72	0	0	0		1	0	1
35		710	10	1	710	0.0014	10	0.986	3	0.995
36		744	0	0	0	0	***	1	0	1
37	January'10	600	120	0	0	0		1	0	1
38		600	48	0	0	0		1	0	1
39		720	24	0	0	0		1	0	1
40		576	144	0	0	0		1	0	1
41		744	0	0	0	0		1	0	1
42		696	24	0	0	0		1	0	1
43		600	120	0	0	0		1	0	1
44		720	24	0	0	0		1	0	1
45		720	24	0	0	0		1	0	1
46		696	0	0	0	0		1	0	1
47		672	24	0	0	0		1	0	1
48		734	48	0	0	0		1	0	1
49	January'11	732	12	0	0	0		1	0	1
50		576	120	0	0	0		1	0	1
51		144	192	0	0	0		1	1	1
52		552	168	1	552	0.0018	168	0.767	50.4	0.916
53		504	216	0	0	0		1	1	1
54		648	72	0	0	0		1	1	1
55		720	24	0	0	0		1	0	1
56		696	48	0	0	0		1	0	1
57		600	120	0	0	0		1	0	1
58		600	120	0	0	0		1	0	1
59		648	72	0	0	0		1	0	1
60		732	12	0	0	0		1	0	1

Table 6: Estimation of availability of Vehicle and structures

Sl. No.	Month	Uptime (hours)	Down time (hours)	No. of failures	MTBF (hours)	Hazard rate	MDT (hours)	A _{OP}	MTTR (hours)	A _{IN}
1	January'07	720	24	0	***	0	***	1	****	1
2		620	12	0	***	0	***	1		1
3		576	144	0	***	0	*	1		1
4		600	120	0	***	0		1		1
5		708	36	0	***	0		1		1
6		700	20	1	700	0.0014	20	0.972	6	0.999
7		734	10	0	***	0		1		1
8		734	10	0	***	0		1	***	1
9		648	72	0	****	0		1		1
10		734	10	0	****	0		1		1
11		672	48	0	***	0		1		1
12		670	24	0	***	0		1	***	1
13	January'08	724	10	0	***	0		1		1
14		686	10	0		0		1		1
15		732	12	0		0		1		1
16		638	82	0		0		1	***	1
17		734	10	1	734	0.0013	10	0.986	3	0.995
18		710	10	1	710	0.0014	10	0.986	3	0.995
19		660	84	0	***	0		1		1
20		710	10	0	****	0		1		1
21		708	12	0	***	0		1	***	1
22		744	0	0		0		1		1
23		624	72	0		0		1		1
24		734	10	0		0		1		1
25	January'09	696	48	0		0		1		1
26		600	72	0		0		1		1
27		733	10	0		0		1		1
28		708	12	0		0		1		1
29		720	0	0		0		1		1
30		696	24	0		0		1		1
31		734	10	0		0		1		1
32		718	26	0	***	0		1		1
33		710	10	0		0		1		1
34		672	72	1	672	0.0014	72	0.903	21.6	0.968
35		710	10	0	***	0		1		1
36		744	0	0		0		1		1
37	January'1	600	120	0		0		1		1
38		600	48	0		0		1	***	1
39		720	24	0		0		1		1
40		576	144	0		0		1		1
41		744	0	0		0		1		1
42		696	24	0		0	****	1		1
43		600	120	0		0		1		1
44		720	24	0		0		1		1

45		720	24	0		0		1		1
46		696	0	0		0		1		1
47		672	24	0		0		1		1
48		734	48	0		0		1		1
49	January'1	732	12	0		0		1		1
50		576	120	0		0	***	1		1
51		144	192	0	***	0		1		1
52		552	168	1	552	0.0018	168	0.767	50.04	0.916
53		504	216	0	***	0		1		1
54		648	72	0		0		1		1
55		720	24	0		0		1		1
56		696	48	0		0		1		1
57		600	120	0		0	****	1		1
58		600	120	0		0	***	1		1
59		648	72	0		0		1		1
60		732	12	0		0		1		1

Table 7: Availability of different components of the Railway Diesel Locomotive Engine

Sl. No.	Name of the Different Components	Availability
1	Compressor	0.998
2	Vehicle and structures	0.997




Figure 9: Availability graph for different components




Figure 10: Availability of compressor




Figure 11: Availability of vehicle and structure

VI. DEVELOPMENT OF SPARES PLANNING AND CONTROL SYSTEM

6.1 Maintenance

The definition often stated maintenance as an activity carried out for any equipment to ensure its reliability to perform its functions [8]. Maintenance to most people is any activity carried out on an asset in order to ensure that the asset continues to perform its intended functions or to repair any equipment that has failed or to keep the equipment running or to restore to its favorable operating condition. Over the years, many new strategies have been implemented as maintenance strategies which are intended to overcome the problems which are related to equipment breakdown. Some of the common maintenance strategies [9] are as follows:-

Table 8: Maintenance Strategy

MAINTENANCE STRATEGY	MAINTENANCE APPROACH	SIGNIFICATION
Corrective Maintenance	Fix it when broke	Large maintenance budget.

Preventive Maintenance	Scheduled Maintenance	Periodic component replacement.
Predictive Maintenance	Condition based Monitoring	Maintenance decision based on equipment condition.
Proactive Maintenance	Detection of sources of failures.	Monitoring and correcting root causes of failure.

6.2 Classification for selective control of spare parts inventory- ABC Analysis

The objective of carrying out ABC analysis is to develop policy guidelines for selective controls of spare parts. The ABC classification of the spare parts of Railway Diesel Engine has been performed on the basis of their annual consumption in rupees. The entire procedure for making ABC analysis is summarized in the following steps:

- Annual consumptions in rupees have been calculated for each spare part.
- The sorting of spare parts has been performed on the basis of annual consumptions in rupees in descending order.
- Cumulative annual usage and cumulative % usage are estimated which are shown in Table 9 .The parts are categorized considering the cumulative % usage.
- The Pareto chart figure 12 is obtained for the spare parts by plotting cumulative percentage usage against the ranks of the parts in descending order to visualize the ABC categories.

Table 9: ABC Analysis of the spare parts

Rank	Spare Part	Annual Usage [In Rupees.]	Cumulative Annual Usage	Cumulative % Usage	Category
1	Compressor	104,17,910.00	104,17,910.00	27.211	A
2	Vehicle and structures	11,97,653.00	38193075.32	99.760	C




Figure 12: Paratoo chart

VII. RESULTS & DISCUSSIONS

7.1 Reliability Estimation

Reliability estimation of the different components of the Locomotive Engine of Railways provides the values of shape parameters as well as reliability (**Table 10**) which focuses on the performance of the components of the Locomotive Engine during the period of January, 2007 to December, 2011.

Table 10: Reliability of the Railway Locomotive Engine components

Sl. No.	Name Of The Different Components	Shape Parameter (B) (From Weibull Plot)	Mean Operating Hour (In Hours)	Reliability	Failure Probability
1	Compressor	6.705	660.102	64.621	35.378
2	Vehicle and structure	7.559	666.628	59.998	40.001




Figure 13: Reliability of different components for Locomotive Engine

From Fig.13, it is found that the estimated Reliability of the different components of the “Railway Diesel Locomotive Engine” is in the range of 59% to 68%. The minimum (59.9987%) reliability is for the vehicle and structure.




Figure 14: Shape parameter of different components

Weibull shape parameter is the indicative of the possible failure mechanism and the causes of failures of any component. Table 11 shows the classification of shape parameters according to their values indicating possible failure mechanism and cause of failure.

Table 11: Classification of shape parameter

Shape Parameter Value	Possible Failure Mechanism	Causes Of Failure
$\beta > 2$	Age related pattern	Accelerated wear and tear of components.
$\beta \approx 1$	Time independent pattern	Process error, design fault, mal operation
$\beta < 1$	Early failure	Manufacturing failure, and reconditioning fault.

The values of the shape parameters of the different components of the Railway Diesel Locomotive engine are given in Table 10 & Fig.13. It is evident that the possible failure mechanism of various components falls into the category of age related pattern and failures occur due to accelerated wear and tear of components (Table 11).

7.2 Availability of Different Components of the Railway Locomotive Engine

As per the definition of operational availability, the availability of different components of the Railway Diesel Locomotive Engine is calculated for a particular month starting from January, 2007 to December, 2011. After that the average operational availability of each component is calculated. A detailed average operational availability of different components of the Railway Diesel Locomotive Engine is given Table 12 and Fig.15.

Table 12: Estimated Operational Availability of the Railway Diesel Locomotive Engine components

Sl. No.	Name of the Different Components	Average Operational Availability
1	Compressor	0.995
2	Vehicle And Structures	0.993




Figure 15: Operational availability of different components

Considering operational availability and inherent availability vs. time period for different components of the Railway Diesel Locomotive Engine (Fig.10 to 11) show the availability patterns of Railway Diesel Engine during the period under study (January, 2007 to December, 2011).

Figure.10: shows that for, Compressor/Exhauster/Brake system both inherent and operational availability are closer to each other for very short periods.

Figure.11: shows that the Vehicle and structures undergoes preventive maintenance and overhauling for shorter period during the months of April 11 to May, 11, as both the inherent and operational availability are coinciding with each other.

7.3 Analyses of the Major Causes of Failures and Recommendations for Their Remedies

After analyzing the failures of the Railway Diesel Locomotive Engine components, the major causes of failures include careless and inexperienced handling, improper and excessive loading, environmental, careless operation, degradation etc

7.4 Proposed Maintenance Schedule

It is true that the failures of the engine parts cannot be fully prevented i.e. 100% availability cannot be achieved, but the probability of failure and frequency of failures, and thus risk can be checked or lowered through proper condition monitoring of the Railway Diesel Locomotive Engine components.

Following are the causes and the recommended preventive measures to be taken for the major components of the engine.

Table 13: Compressor/ exhauster/ brake system

Causes	Corrective actions
Expresser 1 st coupling gasket damaged	Extra care should be taken during major schedule for fitment of 1 st coupling gasket.

Air leakage from expresser side cover gasket due to three nos. over size bolt fitted, caused cover was not tightened properly.	Fitment of standard size bolt should be ensured.
--------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------

Table 14: Vehicle and structure

Causes	Corrective actions
Fro 01 NT trolley side bearer rubber loading pad displaced damage	Replace
Brake rigging damage.	Replace
Gear box problem	Replace

VIII. CONCLUSION

This study has focused mainly on the estimation of the reliability and availability of a specific Railway Locomotive Engine along with maintainability aspects.

The collection of the past data is the most vital precondition to carry out such analysis. The initial stage of the present study has revolved around the collection of well defined data regarding the breakdowns and maintenance of the Engine.

It has been found that worker inefficiency, overloading, degradation of the system components with time are mainly the contributing factors for the failures of Railway Diesel Locomotive Engine.

From the Reliability prediction of the engine components it was found that the reliability of the components ranging from 59% to 68% where maximum reliability found in case of transmission cable (67.998%) and minimum reliability found in case of vehicle and structure (59%). As the maximum systems of the Engine are found to be moderate Reliability and to upgrade its maintenance process of the Locomotive Engine.

The availability patterns describe the performance of the Engine. The plant is having no such correct spare parts provisioning system for a cost effective and timely managed maintenance practice. Whenever any breakdown occurs, the maintenance department places an indent on the requirements for a particular spare part to the store, if the spare is available in the store they supply it to maintenance department and if not, then order is placed to the purchase department as a result maintenance process gets delayed. A spare parts provisioning model has been introduced to estimate the safety stock. In-depth and continuous study it is required to analyzing the effects of the preventive maintenance action for the Railway Locomotive Engine components, controlling and monitoring of spare parts on reliability aspects.

REFERENCES

- [1] E.A. Elsayed, *Reliability Engineering* (Addison Wesley Longman, 1996).
- [2] B. Bhadury and S.K. Basu, *Tero-technology: Reliability Engineering and Maintenance Management-Asian Book Private Limited, 2003, Edition I.*
- [3] L.S. Srinath, *Reliability Engineering* (East West Press, Edition IV, 2005).
- [4] I. Ushakov, Reliability: past, present, future, Recent Advances in Reliability Theory: Methodology, Practice, and Interface, *Birkhauser, Boston*, 2000, pp. 3-14.
- [5] P. Jager and B. Bertsche, A new approach to gathering Failure Behavior Information about Mechanical Components based on Expert Knowledge, *Proc. Ann Reliability & Maintainability Symp.* January-2004, PP 90-95.
- [6] Kales Paul, *Reliability for Technology, Engineering and Management* (Prentice Hall, 1998).
- [7] D. J.Smith, *Reliability Engineering* (Pitman Publishing, 1972).
- [8] Mitchell Leslie, Preventive maintenance and RCM, *IEEE*, 2002.
- [9] W. Nelson, Weibull prediction of a future number of failures, *Quality Reliability Engg. Int.*, vol.16, 2000, pp 23-26.

AUTHORS

Dipankar Bose- Professor, Department of Mechanical Engineering, NITTTR, Kolkata, India.

Ganesh Ghosh- Assistant Manager of DPL, India,
smarttech.mech@gmail.com.

Kingshuk Mandal- Student, Department of Mechanical Engineering, NITTTR, Kolkata, India, *mandal.kingshuk1@gmail.com.*

Sankar Prasad Sau- Student, Department of Computer Science & Technology NITTTR, Kolkata, India, *onlinesankar@gmail.com*

Sandip Kumar- Student, Jadavpur University, Kolkata, India,
sandip.sandip.kumar@gmail.com

Corresponding Author: Sandip Kumar, *sandip.sandip.kumar@gmail.com*, Mobile-9800288336