

Nano IC Engine

Prof. Alka Mata

Mechanical Engg. Department, Siddhivinayak Technical Campus

SAY IC TO NANO!!!!
(NANO - INTERNAL COMBUSTION ENGINE)

Abstract- NANO... one billionth of one and one third of micro, to be precise 10^{-9} m. Nanotechnology is much discussed these days as an emerging frontier – a realm in which machines operate at scales of billionth a metre. It is actually a multitude of rapidly emerging technologies based upon the scaling down of existing technologies to the next level of precision and miniaturization. In the field of nano technologies researchers are enthusiastic about its potential applications in fields such as energy, medicine, electronics, computing and materials. Of late, one of the emerging aspects dealing Nanotechnology in mechanical field is the internal combustion engine on a nano scale, which we have chosen as our area of interest. Heat engines have evolved from external combustion engines to internal combustion engines and the hot off the block is the nano internal combustion engine.

Index Terms- blued, butchery, flash-failure shot, hoggin, end profiling.

I. INTRODUCTION

What is nano technology?

Nanotechnology in mechanical field is the internal combustion engine on a nano scale, which we have chosen as our area of interest. Heat engines have evolved from external combustion engines to internal combustion engines and the hot off the block is the nano internal combustion engine.

Its worth pointing out that the word nanotechnology has become very popular and is used to describe many types of research where the characteristic dimension are less than about thousand nano meter. If we are to continue these trends we will have to develop a new manufacturing technology which will let us inexpensively build nano system with mole quantities that are molecular in both size and precision and are inter connected in complex patterns NANO TECHNOLOGY WILL DO THIS.

What is heat engine?

Heat engines work on the principle of converting chemical energy into mechanical work and evolve from external combustion engine to internal combustion engine. External combustion engine is the heat engine in which fuel combustion takes place external to cylinder. Due to this it is bulky and consumes lot of place. Second revolution of heat engines are ICE in which fuel combustion takes internally and consumes less place and became compact, cost effective. Of late third revolution is **NANO Internal Combustion Engine**. It is difficult to thread- in a needle.

II. IDENTIFY, RESEARCH AND COLLECT IDEA



Figure 1

This picture gives an idea of the size of the nano internal combustion engine. If you observe, the length from the back plate to washer is less than an inch. There are no exotic materials required

It has high precision, cost effective, high speed [up to 40000rpm].The various applications can be spotted from race cars to space crafts. It can also be applied to various fields like agricultural pump sets, industrial applications, Hospitals, constructions civil engineering equipments etc.,

This paper further deals with the history, construction of a nano IC engine, their merits & their future prospects. This paper discuss about Nano IC engine at length.



Figure 2

The *Nano* is a 0.1cc (that's less than 0.01 cuin) compression ignition engine - most frequently, if somewhat inaccurately, referred to as a "diesel". It was designed by Richard Gordon and the plans were



Figure 3

An idea of the size of the *Nano* is given by this picture. From backplate to drive washer is less than 1 inch. There are no exotic materials required. The crankcase is hacked from a solid cube of aluminium 3/4" on a side. The piston and contra piston are cast iron. The crankshaft and liner are any old steel from the scrap box.



Figure 5

Here is an exploded view of the engine. The odd looking thing in the foreground is a special Nano-Spanner required to tighten the backplate. It also fits the fuel nipple. The construction is extremely conventional - only the scale is unusual.



Figure 6

Like all model IC projects, there are a few special jigs and tools required to construct the Nano. All are fully detailed in the plan, which includes step by step instructions with photos. The cutter is made from water hardening drill rod (called "silver steel" in the UK because of its appearance - it contains no silver).the teeth are formed of Dremal-type cut-off wheel.



Figure 7

The cutter is used to form the exhaust ports in the cylinder. There are three of these, spaced at 120 degrees with sufficient space between them for the angled transfer ports to slightly overlap the timing. The crown of the piston is conical to assist transfer. The contra piston has a matching concave conical depression.



Figure 8

There's nothing special in the crankshaft components. Another jig (not shown) is made to hold the shaft in the 3-jaw chuck, offset by half the throw for forming the crank pin. Even at these sizes, final lapping to size is no different from larger engines in terms of the amount of metal that must be LEFT for removal. Only the microscopic size makes things difficult. The prop driver knurls were formed with a thread form tool, set on edge and used as a shaper.



Figure 9

Again, apart from their size, there's nothing special about the needle valve components the needle itself was made from steel and "blued" it by a quick heat in a gas flame followed by water quenching. No big deal, but the amazing thing is the attention it draws with people who examine the engine. When it was fired, it run briefly, oscillating back and forth about TDC like over compressed diesels with small mass fly wheels are wont to do. running! .but spring starters are the only way to start ultra small diesels - hand propping just won't work. Also, the fuel for mini diesels needs a lot of ether - as high as 50% by volume. With high ether fuel and a spring starter, the little Nano will burst into life. Richard Gordon claims it will turn 40,000 rpm - yes, that's no typo, *forty thousand revolutions per minute*. American engine builder Ron Colona used to demo his at model engineering shows and turning at better than 20,000 rpm.

III. THE COMPONENTS USED

1)Crankcase and Cylinder rough-out



Figure 10

The crankcase starts off as a chunk of aluminum bar of about 1-1/2" diameter, sawn to length, plus a little bit. The first step is to finish turn the front section with a 1/4" radius where the journal blends into the body. The photo shows the roughing out process. Note that the tool is raked back sharply while "hoggin' great cuts" are made so that if it digs in, the cut will be forced shallower, not deeper compass could achieve the same result with about the same effort.

2) **Backplate**



Figure 11

The backplate is simple turning with only some aspects of work holding posing any problems. In this first shot, the backplate profile has been turned on a piece of bar stock with the interior face oriented towards the tailstock. This means we will be screwcutting towards the shoulder formed by the backplate rim, so a thin (0.020") runout groove is first cut at the thread/rim junction to the depth of the thread form. This also assures the backplate will form a tight seal against the rear of the crank case. The thread cutting tool is a piece of 1/4" diameter HSS steel, ground to a 60 degree point with seven degrees of side rake, mounted in a tracting tool holder. This magnificent gadget takes a while to make but is absolutely invaluable to thread cutting. The little ball lever actuates a spring loaded, over center cam - just requiring a flick to retract the tool bit by about 3/16". This allows the saddle to be repositioned for the next cutting pass without having to twiddle dials and remember settings.

3) **Venturi and Needle Valve Assembly**

In the previous section, the cylinder had progressed to a nearly finished state, still requiring internal lapping. Lapping should always be the last operation on a cylinder of this type. This means the boss for attaching the side port venturi must be fitted before lapping can be done. In this session, the boss is made and the associated parts for the venturi and needle valve. The boss will be soft soldered to the cylinder (diesels don't get hot enough to melt soft solder). ".solder does not make the joint, it only keeps the air out" and schooled me to make a good fit of parts to be soldered. The boss will butt to the cylinder, which has an outside diameter of 0.500". So, a good fit can be achieved by profiling the boss with a 1/2" end mill. In this photo, we see the boss blank (enough for four) which has been finished outside, drilled ready for tapping and transferred still in the 3 jaw chuck to the mill for end profiling.

IV. APPLICATIONS

- It can be controlled in aero planes/satellites/space ships etc., the timing of in let and exhaust valves.

- According to NASA reports they are experimenting about the use of nano engine in nano & pico satellites.
- In case of a mine tragedy where harmful gases are emitted ,these nano ic engines can be employed as powerful blowers to blow out these gases is a less time saving the lives of trapped miners .We require atleast 5-6 blowers to blow these gases where as two nano ic engines could do the tick in less time.

V. RESEARCH

Every day people are spending more and more money because of rising gas prices. People all over the world are trying to find a solution—even visiting websites to locate the nearest and cheapest gas, all the while losing time and mileage just to reach [these] refueling stations. Many have been giving up favorite hobbies and changing life plans because of the need to reallocate their funds for gas. For those of us who must drive to work or school, it seems we have little choice but to continue paying more. Now, there is a way to fight back against these constant increases in gas prices—and to fight pollution and protect the environment in the process.

The solution

Use the most advanced technology available to improve fuel economy, prolong the engine life, reduce harmful emissions and protect the environment. The number one product for fuel economy, power and pollution control is now available .

Introducing our two unique nanotechnology products:

F2-21 NanoLube Engine Oil Treatment, and
F2-21 NanoRon Gas & Diesel Fuel Enhancer.

With nanotechnology, fuel transforms at the nano-level to achieve a more complete combustion, resulting in increased fuel economy, more driving power, and fewer pollutive emissions.

Use either product or both to get multiple benefits:

- Adds great power to your engine. NanoLube eases heavy driving loads and increases driving pleasure with a faster, smoother, and quieter ride.
- Boosts miles per gallon (analogous to buying Premium Gas or boosting your octane number), while saving you money and conserving energy.
- Prolongs engine life by cleaning your combustion chamber and piston ring deposits, extending engine life and cutting equipment downtime.
- Protects the environment by reducing harmful emissions and fighting global warming.

VI. CONCLUSION

With the application of Nano in every sphere of life the 'big' may not find its place in engineering dictionary in future. If we are to continue these trends we will have to develop a new manufacturing technology, which will let us inexpensively build nano system with mole quantities that are molecular in both size and precision and are, inter connected in complex patterns NANO TECHNOLOGY WILL DO THIS. NANO technology

with all its challenges and opportunities is an avoidable part of our future. It can be rightly said that nano technology slowly and steadily assuring in the next Industrial Revolution.

[3] www.seminarsonly.com

[4] www.Bbc.co.uk

REFERENCES

[1] www.alibaba.com

[2] www.autoanything.com

AUTHORS

First Author – Prof. Alka Mata, B.E.(Mech), M.E.(CAD-CAM)(app.), Siddhivinayak Technical Campus, Khamgaon.
e-mail:-mataalka@yahoo.co.in