

# Potential Utilization of Waste and Local Plants as Absorbents of Fe and Mn in Dug Well Water

Husaini\*, Anugrah Nur Rahmat\*, Muhammad Saidi Hidayat\*\*, M. Gilmani\*\*, Taufik\*\*

\*Department of Environmental Health, Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

\*\*Student of Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

DOI: 10.29322/IJSRP.12.11.2022.p13119  
<http://dx.doi.org/10.29322/IJSRP.12.11.2022.p13119>

Paper Received Date: 28th September 2022

Paper Acceptance Date: 30th October 2022

Paper Publication Date: 14th November 2022

**Abstract-**Water is the main need in life so that every living thing can grow and develop properly on earth. Riskesdas 2018 data shows that the proportion of clean water usage < 20 l/person/day is 2.2%, meaning that in Indonesia there are still 2.2% where access to clean water is very lacking and minimal. Data for South Kalimantan with very poor access is about 3% and for Banjar Regency as much as 2.41% with details < 5 liters 0.43% meaning that access is very low, the health risk is very high, 5-19,9% as much as 1.98 l/ people/day means less access, high health risk. The potential of plants and waste resulting from seasonal community activities in the environment can be used as activated carbon such as charcoal and ash, which can adsorb certain gases and chemical compounds or have selective adsorption properties, depending on the size or volume of pores and surface area because the adsorption capacity of activated carbon is very large, which is 25-1000% by weight of activated carbon. Activated carbon is often used to reduce organic contaminants, synthetic organic chemical particles, but activated carbon is also effective for reducing inorganic contaminants such as radon, mercury, iron, manganese and other toxic metals. So it is necessary to treat clean water in the Astambul sub-district in order to fulfill the physical, chemical, bacteriological quality, namely by filtration and adsorption methods can use natural materials that grow such as water hyacinth and Moringa and the rest of community activities around the community such as rice straw, husks, coconut fibers, coconut shells, market charcoal. Each has advantages in improving water quality, such as Moringa leaves (*Moringa oleifera*) can be used to purify water because they contain nine amino acids, sucrose, D-glucose, alkaloids, wax, quercetin and kaempferate are also rich in potassium and calcium. . Moringa leaves contain vitamins, carotenoids, polyphenols, phenolic acids, flavonoids, alkaloids, glucosinolates, isothiocyanates, tannins, saponins, and oxalates.

**Index Terms-** potential, plants (moringa leaves, water hyacinth, purun rat), waste from seasonal activities (coconut shells, straw, husks, rice leaves) rice husks

## I. INTRODUCTION

Water is the main need in life so that every living thing can grow and develop properly on earth (1). Riskesdas 2018 data shows that

the proportion of clean water usage < 20 l/person/day is 2.2%, meaning that in Indonesia there are still 2.2% where access to clean water is very lacking and minimal. Data for South Kalimantan with very poor access is about 3% and for Banjar Regency as much as 2.41% with details < 5 liters 0.43% meaning that access is very low, the health risk is very high, 5-19,9% as much as 1.98 l/ people/day means less access to high health risk (Riskesdas, 2018). Efforts are being made to overcome the problem of the availability of clean water by empowering the community. Community empowerment is carried out in order to meet the physical, chemical, bacteriologically, namely by filtration and adsorption methods can use natural materials that grow such as water hyacinth and moringa and the rest of community activities around the community such as rice straw, husks, coconut fibers, coconut shells, market charcoal. The active ingredient content in water hyacinth consists of 60% cellulose, 8% hemicellulose, and 17% lignin. , fat 1.33%. Moringa leaves contain vitamins, carotenoids, polyphenols, phenolic acids, flavonoids, alkaloids, glucosinolates, isothiocyanates, tannins, saponins, and oxalates. The active ingredients in these local ingredients are useful for filtering water from impurities and helping in overcoming pollutants in the water so that the water becomes clear. Astambul sub-district has several weaknesses, namely the availability of clean water is lacking, and the quality of surface water does not meet the requirements as clean water both physically, chemically and bacteriologically. The strength it has is the availability of locally available resource materials such as rice straw, husks, coconut fibers, coconut shells, market charcoal. Opportunities that are owned are local resources available in abundance and easy to obtain. Then the threat that is owned is that there are local resources that are not durable, so they must be managed immediately. The cause of Banjar Regency frequent flooding is because the low location of Banjar Regency from above sea level causes the flow of water on the ground surface to be hampered. As a result, some areas are always inundated (29.93%) while others (0.58%) are periodically inundated (2). According to Rahman in 2017, areas that are categorized as highly prone to flooding are routinely located on slopes of 0 - 8% with an average annual rainfall of 18.69 - 21.5 mm/day. This area consists of sub-districts in Banjar Regency, one of which is Astambul (3). The proposal of this research is to test

the potential of clean water treatment made from local materials to improve the quality and quantity of Fe and Mn in clean water in post-flood fulfillment.

## II. RESEARCH METHODS

The instruments that will be used in this research are in the form of filling sheets, and questionnaires and water testing laboratory equipment. Carry out absorption activities with physical media and waste consisting of coconut shells, straw, husks, Moringa leaves, water hyacinth.

## III. RESULTS AND DISCUSSION

**Table 1 Soil Test Results in Astambul District in 6 villages (Kelampian Tengah, Kelampayan Ulu, Lok Gabang, Sungai Alat and Kaliukan)**

No	Sample	Soil				
		Organic Carbon (%)	Organic Ingredients (%)	Mn-soluble (PPM)	Fe-soluble (PPM)	Permeability (cm/hour)
<b>Middle Kelampian Village</b>						
1	1 point	2.09	3.6	14	57.38	7.64
2	Point 2	1.38	2.41	3.91	12.68	3.36
3	3 point	1.25	2.17	4.48	13.61	2.3
4	4 point	0.69	1.2	3.62	22.45	2.64
5	5 point	0.88	1.54	3.57	8.75	1.92
<b>Average</b>		<b>1.26</b>	<b>2.18</b>	<b>5.92</b>	<b>22.97</b>	<b>3.57</b>
<b>Lok Gabang Village</b>						
6	1 point	2.01	3.46	15.4	32.29	4.84
7	Point 2	1.3	2.26	2.91	5.77	2.33
8	3 point	0.41	0.72	2.78	15	1.94
9	4 point	0.63	1.1	2.78	6.41	2.3
10	5 point	1.23	2.13	2.27	5.63	1.97
11	6 point	1.33	2.32	2.91	7.64	2.34
<b>Average</b>		<b>1.15</b>	<b>2.00</b>	<b>4.84</b>	<b>12,12</b>	<b>2.62</b>
<b>Tool River Village</b>						
12	1 point	1.54	2.66	42	66.12	1.02
13	Point 2	0.21	0.36	3.94	12.78	4.52
14	3 point	1.59	2.77	2.76	29.59	2.66
15	4 point	1.13	1.97	3.05	7.03	2.8
16	5 point	0.65	1.13	3.79	31.9	2.44
17	6 point	0.88	1.54	49.14	1217.94	2.57
18	7 point	0.94	1.63	3.94	10.08	2.67
<b>Average</b>		<b>0.99</b>	<b>1.72</b>	<b>15.52</b>	<b>196.49</b>	<b>2.67</b>
<b>Kaliukan Village</b>						
19	1 point	0.14	0.25	62.3	36.36	2.8
20	Point 2	0.48	0.84	2.28	10.62	1.86
21	3 point	0.73	1.27	2.37	5.87	2.32
22	4 point	1.12	1.94	2.71	7.89	2.09
23	5 point	1.59	2.77	3.06	6.06	2.25
24	6 point	0.84	1.45	2.76	19.82	2.57

No	Sample	Soil				
		Organic Carbon (%)	Organic Ingredients (%)	Mn-soluble (PPM)	Fe-soluble (PPM)	Permeability (cm/hour)
<b>Average</b>		<b>0.82</b>	<b>1.42</b>	<b>12.58</b>	<b>14.44</b>	<b>2.32</b>
Ulu						
25	1 point	2.21	3.82	23.8	48.84	4.08
26	Point 2	1.26	2.2	3.12	15.61	2.67
27	3 point	1.55	2.7	3.68	13.78	2.66
28	4 point	2.14	3.73	3.13	17.46	2.34
29	5 point	1.66	2.9	2.89	3.88	2.67
30	6 point	1.29	2.24	3.67	12.92	1.94
<b>Average</b>		<b>1.69</b>	<b>2.93</b>	<b>6.72</b>	<b>18.75</b>	<b>2.73</b>
<b>Overall Average</b>	<b>Land</b>	<b>1.18</b>	<b>2.05</b>	<b>9.11</b>	<b>52.95</b>	<b>2.78</b>

Soil sample testing in 5 villages of Astambul District was seen based on 6 indicators, namely organic carbon, organic matter, water content, soluble Mn, soluble Fe and permeability. The average value of soil organic carbon from all sampling points is 1.09%. The highest value is at point 3 in Kelampayan Ulu Village at 2.14% and the lowest at point 2 in Lok Gabang Village at 0.41%. The average value of organic matter for all points of collection was 1.9%. The village with the highest average score is Kelampayan Ulu Village at 2.75% and the highest point is at point 3 Kelampayan Ulu Village at 3.73%. The water content in the soil for all points has an average of 21.03%. Kaliukan Village has the highest average water content of 26.85% and the point with the highest water content is also found in Kaliukan Village at point 1 of 34.56%. The average soluble Mn content for all points was 4.73ppm. Villages with the highest average soluble Mn content were found in Sungai Alat Village at 11.10 ppm and the point with soluble Mn levels was at point 5 in Sungai Alat Village at 49.14 ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. Villages with the highest average soluble Mn content were found in Sungai Alat Village at 11.10 ppm and the point with soluble Mn levels was at point 5 in Sungai Alat Village at 49.14 ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. 14ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. 14ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. 14ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour. 14ppm. The average soluble Fe content for all points was 52.69ppm. The village with the highest soluble Fe content was found in Sungai Alat Village at 218.22 ppm and the point with the highest soluble Fe content was also found in Sungai Alat village point 5 at 1217.94 ppm. The average soil permeability from all points is 2.47cm/hour. The village with the highest average level of soil permeability is in Sungai Alat Village of 2.94cm/hour and the highest point of soil permeability is at point 1 in Sungai Alat Village of 4.54 cm/hour.

Soil organic carbon (C) is a fundamental component in the global carbon cycle to support the sustainability of terrestrial ecosystems. Soil C-organic is formed through several stages of organic matter decomposition. Soil C-organic status is influenced by various external factors such as soil type, rainfall, temperature, input of organic matter from above-soil biomass, anthropogenic processes, soil management activities, and CO<sub>2</sub> content in the atmosphere. Changes in soil C-organic status through the process of decomposition and

Mineralization of soil organic matter is reported to be related to soil properties such as texture, pH, metal cations in the soil, CEC (cation exchange capacity), and nitrogen content (4).

Organic matter can be defined as all materials derived from plant and animal tissues, both living and dead. Soil organic matter is a complex and dynamic material, derived from the remains of plants and animals in the soil and undergoing continuous degradation. Soil organic matter is formed from living soil organisms consisting of flora and fauna, living and dead plant roots, which are decomposed and modified as well as new synthesis products derived from plants and animals. Soil organic matter plays an important role in determining the physical, chemical, and biological activities in the soil that determine the carrying capacity and productivity of the land. Organic matter is generally found on the soil surface in the amount of only 3-5% (5).

Organic matter is a complex and dynamic system, sourced from plant or animal residues found in the soil that continuously changes shape, because it is influenced by physical, biological, and chemical factors. Reintjes et al., (1992 in Nangaro) suggested that the function of soil organic matter, among others, is to store nutrients which are slowly released into the groundwater solution and made available to plants. Organic matter in or above the soil also protects and helps regulate soil temperature and humidity. Organic matter can also increase soil support (5).

The results showed that degraded paddy fields were one of the indications due to low organic matter and potassium. Organic matter has an important role in determining the ability of the soil to support plants, so that if the level of soil organic matter decreases, the ability of the soil to support plant productivity also decreases (6).

The C-Organic content of the soil can be low because the absence of the use of organic fertilizers in a field is the main factor in the low C-organic content of the soil. The land only uses inorganic fertilizers to increase soil fertility (7).

Soil water content is the ability of the soil to bind water which is influenced by matrix, osmotic and capillary binding forces. These forces are caused by the attraction between soil particles to one another and is also influenced by the electrostatic charge density of the soil particles. The disturbance and changes in volume weight, soil pore volume and pore size distribution cause variations in water content in the soil. The value of water content can be obtained by gravimetric method, namely the weight of the initial wet soil with the weight of the oven dry soil (8).

**Table 3. Results of inspection of the physical quality of clean water in Astambul District in 5 villages (Kelampian Tengah, Kelampayan Ulu, Lok Gabang, Sungai Alat and Kaliukan)**

No	Sample	Physique							
		Temperature (Maximum Level=Air Temperature ±3)	DO (Level 6)	(Minimum)	TDS (Maximum Level=1000)	Turbidity (Maximum Level=25)			
<b>Middle Kelampian Village</b>									
1	1 point	35.5	it is not in accordance with	7.5	in accordance	181	in accordance	7.44	in accordance
2	Point 2	28	in accordance	4	it is not in accordance with	131	in accordance	4.74	in accordance
3	3 point	27	in accordance	3.5	it is not in accordance with	188	in accordance	8.3	in accordance
4	4 point	28	in accordance	2.2	it is not in accordance with	251	in accordance	3.52	in accordance
5	5 point	27	in accordance	8.1	in accordance	112	in accordance	14.97	in accordance
<b>Average</b>		<b>29.10</b>	<b>in accordance</b>	<b>5.06</b>	<b>it is not in accordance with</b>	<b>172.6</b>	<b>in accordance</b>	<b>7.79</b>	<b>in accordance</b>
<b>Lok Gabang Village</b>									
6	1 point	31.5	in accordance	1.8	it is not in accordance with	287	in accordance	48.25	it is not in accordance with
7	Point 2	27	in accordance	5.6	it is not in accordance with	178	in accordance	17.46	in accordance
8	3 point	27	in accordance	20	in accordance	127	in accordance	11.62	in accordance

No	Sample	Physique							
		Temperature (Maximum Level=Air Temperature $\pm 3$ )	DO (Minimum Level 6)	TDS (Maximum Level=1000)	Turbidity (Maximum Level=25)				
9	4 point	28	in accordance	14.4	in accordance	95	in accordance	11.4	in accordance
10	5 point	28	in accordance	3.8	it is not in accordance with	148	in accordance	34.5 5	it is not in accordance with
11	6 point	27	in accordance	4.8	it is not in accordance with	185	in accordance	27.3	it is not in accordance with
<b>Average</b>		<b>28.0 8</b>	<b>in accordance</b>	<b>8.40</b>	<b>in accordance</b>	<b>170</b>	<b>in accordance</b>	<b>25,1 0</b>	<b>it is not in accordance with</b>
Tool River Village									
12	1 point	30.3	in accordance	1.4	it is not in accordance with	162	in accordance	6	in accordance
13	Point 2	28	in accordance	5.5	it is not in accordance with	159	in accordance	30.7 7	it is not in accordance with
14	3 point	27	in accordance	6.1	in accordance	158	in accordance	49.5 6	it is not in accordance with
15	4 point	27	in accordance	6.2	in accordance	231	in accordance	20.7 8	in accordance
16	5 point	27	in accordance	6.7	in accordance	105	in accordance	6.43	in accordance
17	6 point	27	in accordance	32.1	in accordance	258	in accordance	33.0 9	it is not in accordance with
18	7 point	29	in accordance	2.6	it is not in accordance with	86	in accordance	5.16	in accordance
<b>Average</b>		<b>27.9 0</b>	<b>in accordance</b>	<b>8.66</b>	<b>in accordance</b>	<b>165.5 7</b>	<b>in accordance</b>	<b>21.6 8</b>	<b>in accordance</b>
Kaliukan Village									
19	1 point	35.9	it is not in accordance with	5.3	it is not in accordance with	339	in accordance	6.08	in accordance
20	Point 2	28	in accordance	31	in accordance	119	in accordance	30,1 9	it is not in accordance with
21	3 point	27	in accordance	8.4	in accordance	177	in accordance	23.3 5	in accordance
22	4 point	28	in accordance	4.3	it is not in accordance with	87	in accordance	4.31	in accordance
23	5 point	27	in accordance	8.1	in accordance	71	in accordance	17.0 1	in accordance
24	6 point	27	in accordance	19.2	in accordance	93	in accordance	21.8 2	in accordance

No	Sample	Physique							
		Temperature (Maximum Level=Air Temperature $\pm 3$ )	DO (Minimum Level 6)	TDS (Maximum Level=1000)	Turbidity (Maximum Level=25)				
<b>Average</b>		<b>28.8</b>	<b>in accordance</b>	<b>12.7</b>	<b>in accordance</b>	<b>147.6</b>	<b>in accordance</b>	<b>17.1</b>	<b>in accordance</b>
Ulu Kelampayan Village									
25	1 point	34.3	it is not in accordance with	3.1	it is not in accordance with	261	in accordance	10.4	in accordance
26	Point 2	29	in accordance	3.3	it is not in accordance with	296	in accordance	2.22	in accordance
27	3 point	27	in accordance	5.4	it is not in accordance with	276	in accordance	12.6	in accordance
28	4 point	27	in accordance	4.4	it is not in accordance with	223	in accordance	41.9	it is not in accordance with
29	5 point	26	it is not in accordance with	8.8	in accordance	223	in accordance	14.2	in accordance
30	6 point	27	in accordance	6.9	in accordance	164	in accordance	5.38	in accordance
<b>Average</b>		<b>28.3</b>	<b>it is not in accordance with</b>	<b>5.32</b>	<b>it is not in accordance with</b>	<b>240,5</b>	<b>in accordance</b>	<b>14.4</b>	<b>in accordance</b>
<b>Overall Physical Average</b>		<b>28.4</b>	<b>in accordance</b>	<b>8.03</b>	<b>in accordance</b>	<b>179.2</b>	<b>in accordance</b>	<b>17.2</b>	<b>in accordance</b>

Source: Primary Data 2022

a) Temperature

The results of testing water samples at 30 points spread across Astambul District found that the water temperature was suitable for sanitation hygiene purposes according to the Minister of Health Regulation Number 32 of 2017. However, there were 4 points (13.33%) which had water temperatures below the standard of the regulations in the village. Kelampayan Tengah, Kaliukan Village and Kelampayan Ulu Village.

The temperature of the water is very dependent on the place where the water is located. The increase in water temperature in water bodies, waterways, rivers, lakes and so on will have consequences in the form of 1) The amount of dissolved oxygen in the water decreases; 2) The speed of chemical reactions increases; 3) The life of fish and other aquatic animals is disturbed (9). Water temperature that exceeds normal limits indicates that there are dissolved chemicals in large enough quantities (eg phenol or sulfur) or that the process of decomposition of organic matter by microorganisms is taking place. If the condition of the water is like that then the water is said to be unfit for drinking and can interfere with health (10).

b) DO (Dissolved Oxygen)

Dissolved Oxygen (DO) testing on water samples in Astambul District obtained an average of 8.03 mg/l and is in accordance with the water used for sanitation hygiene needs. At some points, the number of DO is still below the standard, namely 16 points (53.3%) and spread over 6 villages (Kelampayan Tengah, Kelampayan Ulu, Lok Gabang, Sungai Alat, and Kaliukan).

Dissolved Oxygen (DO) is the amount of oxygen dissolved in a certain volume of water at a certain temperature and pressure. DO in water is needed to support the life of the organisms in it (Saksena et al., 2008). The main source of DO is photosynthesis, besides river characteristics also affect the presence of DO. The characteristic of the river which is relatively flat shows a flow pattern that is relatively calm and there is no turbulence which will reduce the process of re-aeration of air into the water so that the process of diffusion of oxygen into the river water is not optimal (11).

c) TDS (Total Dissolved Solid)

The average value of Total Dissolved Solid (TDS) obtained is 179.27 mg/l and is in accordance with the water requirements used for sanitation hygiene needs according to the Minister of Health Regulation No. 32 of 2017. There were no sampling points that had the amount of TDS exceeding the maximum threshold.

Total Dissolved Solids (TDS) are dissolved materials (10-6mm diameter) and colloids (10-6mm-10-3mm diameter) in the form of chemical compounds and other materials that are not filtered on filter paper. 0.45 m in diameter (12).

d) Turbidity

The results of the turbidity level test obtained an average of 17.23NTU. This figure is below the maximum threshold for water used as sanitation hygiene so that in terms of turbidity it still meets the standard. However, there are 8 points (26.67%) which have a high level of turbidity or above 25NTU so that it does not meet the feasibility of water used for sanitation hygiene according to Minister of Health Regulation No. 32 of 2017.

The turbidity value indicates that the river water is not suitable for consumption. The turbidity of river water is caused by the amount of material suspended in the river water, such as soil, mud and other organic materials. Suspended sediment from land is carried by surface runoff when it rains (13).

1) Chemical testing

Sampling of water for chemical testing at 30 points spread over 5 villages in the Astambul District, the results can be seen in the following table.

**Table 4** The results of the chemical quality inspection of clean water in Astambul District in 5 villages (Kelampian Tengah, Kelampayan Ulu, Lok Gabang, Sungai Alat and Kaliukan)

No	Sample	Chemical								
		pH (Recommended Level=6.5-8.5)	Iron (Maximum Level=1mg/l)	Manganese (Maximum Level=0.5mg/l)	Lead (Maximum Level=0.05mg/l)					
Middle Kelampian Village										
1	1 point	6.4	it is not in accordance with	0.756	in accordance	18.4	it is not in accordance with	32.447pg/l	in accordance	
2	Point 2	6.3	it is not in accordance with	1.03	it is not in accordance with	21.2	it is not in accordance with	31,596pg/l	in accordance	
3	3 point	6.3	it is not in accordance with	1.054	it is not in accordance with	21.8	it is not in accordance with	38,511pg/l	in accordance	
4	4 point	6.7	in accordance	0.982	in accordance	25	it is not in accordance with			
5	5 point	6	it is not in accordance with	0.371	in accordance	28.98	it is not in accordance with			
<b>Average</b>		<b>6.34</b>	<b>it is not in accordance with</b>	<b>0.84</b>	<b>in accordance</b>	<b>23.08</b>	<b>it is not in accordance with</b>	<b>34.18</b>	<b>in accordance</b>	
Lok Gabang Village										
6	1 point	6.4	it is not in accordance with	0.621	in accordance	20.6	it is not in accordance with	21.17pg/l	in accordance	
7	Point 2	6.2	it is not in accordance with	0.809	in accordance	25	it is not in accordance with			
8	3 point	6.3	it is not in accordance with	0.352	in accordance	21.8	it is not in accordance with	25,213pg/l	in accordance	
9	4 point	6.3	it is not in accordance with	0.558	in accordance	13.2	it is not in accordance with			

No	Sampl e	Chemical							
		pH (Recommended Level=6.5-8.5)	Iron (Maximum Level=1mg/l)	Manganese (Maximum Level=0.5mg/l)	Lead (Maximum Level=0.05mg/l)				
10	5 point	6.4	it is not in accordance with	0.732	in accordance	23	it is not in accordance with	25.532pg/l	in accordance
11	6 point	6.10	it is not in accordance with	0.371	in accordance	19.53	it is not in accordance with		
<b>Average</b>		<b>6.28</b>	<b>it is not in accordance with</b>	<b>0.57</b>	<b>in accordance</b>	<b>20.52</b>	<b>it is not in accordance with</b>	<b>23.97</b>	<b>in accordance</b>
Tool River Village									
12	1 point	5.2	it is not in accordance with	0.549	in accordance	24.4	it is not in accordance with	40.957pg/l	in accordance
13	Point 2	5.9	it is not in accordance with	0.799	in accordance	22.8	it is not in accordance with		
14	3 point	5.4	it is not in accordance with	1.395	it is not in accordance with	10.6	it is not in accordance with	48.085pg/l	in accordance
15	4 point	6.7	in accordance	0.943	in accordance	12.8	it is not in accordance with		
16	5 point	6.4	it is not in accordance with	0.684	in accordance	24.4	it is not in accordance with		
17	6 point	6.3	it is not in accordance with	0.491	in accordance	19.6	it is not in accordance with	49,681pg/l	in accordance
18		8.35	in accordance	0.116	in accordance	14.49	it is not in accordance with		
<b>Average</b>		<b>6.32</b>	<b>it is not in accordance with</b>	<b>0.71</b>	<b>in accordance</b>	<b>18.44</b>	<b>it is not in accordance with</b>	<b>46.24</b>	<b>in accordance</b>
Kaliukan Village									
19	1 point	6.4	it is not in accordance with	0.698	In accordance	25	it is not in accordance with	32,021pg/l	in accordance
20	Point 2	6.9	in accordance	0.905	In accordance	24.4	it is not in accordance with		
21	3 point	6.2	it is not in accordance with	0.943	In accordance	24.2	it is not in accordance with	38,511pg/l	in accordance
22	4 point	6.4	it is not in accordance with	0.785	In accordance	24.6	it is not in accordance with		
23	5 point	6.4	it is not in accordance with	0.496	In accordance	20.6	it is not in accordance with	44,255pg/l	in accordance
24	6 point	8.27	in accordance	0.087	in accordance	12.6	it is not in accordance with		



No	Sampl e	Chemical							
		pH (Recommended Level=6.5-8.5)	Iron (Maximum Level=1mg/l)	Manganese (Maximum Level=0.5mg/l)	Lead (Maximum Level=0.05mg/l)				
<b>Average</b>		<b>6.76</b>	<b>in accordance</b>	<b>0.65</b>	<b>in accordance</b>	<b>21.90</b>	<b>it is not in accordance with</b>	<b>38.26</b>	<b>in accordance</b>
Ulu Kelampayan Village									
25	1 point	6.9	in accordance	0.4	In accordance	12.8	it is not in accordance with	61,277pg/l	in accordance
26	Point 2	6.2	it is not in accordance with	0.809	In accordance	25	it is not in accordance with		
27	3 point	6.3	it is not in accordance with	1.063	it is not in accordance with	19.6	it is not in accordance with		
28	4 point	6.4	it is not in accordance with	0.669	In accordance	25	it is not in accordance with	53,936pg/l	in accordance
29	5 point	6.7	in accordance	0.472	In accordance	17.4	it is not in accordance with	60.532pg/l	in accordance
30	6 point	6.6	in accordance	0.371	in accordance	27.09	it is not in accordance with		
<b>Average</b>		<b>6.52</b>	<b>in accordance</b>	<b>0.63</b>	<b>in accordance</b>	<b>21.15</b>	<b>it is not in accordance with</b>	<b>58.58</b>	<b>in accordance</b>
<b>Overall Chemistry Average</b>		<b>6.44</b>	<b>it is not in accordance with</b>	<b>0.68</b>	<b>in accordance</b>	<b>21.02</b>	<b>it is not in accordance with</b>	<b>40.25</b>	<b>in accordance</b>

Source: Primary Data 2022

a) pH level

The value of the degree of acidity or pH of the test results from 30 points spread across Astambul District is an average of 6.44 mg/l so that most of the water sources in Astambul District are acidic. This figure is below the standard of water used for sanitation hygiene purposes.

The pH value is an important factor in waters because the pH value in the water will determine the nature of the water to be acidic or alkaline which will affect the biological life in the water (11). According to the Minister of Health Regulation Number 32 of 2017 which states that the standard pH or acidity degree for water used as sanitation hygiene is in the range of 6.5-8.5.

b) Iron

The content of iron (Fe) in the water as a result of testing at 30 points in Astambul District obtained an average of 0.68mg/l. The content of this amount is still below the maximum threshold for water used as a means of sanitation and hygiene. However, there are 4 points (13.33%) where the iron content is higher than the standard.

High levels of Fe metal have an impact on the color of groundwater, where for groundwater samples with the highest Fe metal content it has a brownish color, while water samples with the lowest Fe metal content have a yellowish color. In general, rainwater that falls to the ground and undergoes infiltration into the soil containing FeO will react with H<sub>2</sub>O and CO<sub>2</sub> in the soil and form Fe(HCO<sub>3</sub>)<sub>2</sub> where the deeper the water that seeps into the soil, the higher the solubility of iron carbonate. in that water. Groundwater that contains a lot of Fe will turn yellow and cause a metallic taste of Fe in the water and corrode metal objects. The presence of Fe in the water can cause the water to turn yellowish red and cause an unpleasant odor (14).

c) Manganese

The results of testing water samples to see the manganese or Mn content in the water obtained an average of 21.02 mg/l. Very far beyond the maximum threshold set for water used as sanitation hygiene by the community. There is no point that has Mn content according to the standard.

Water containing excess Manganese (Mn) causes taste, color (brown/purple/black), and turbidity. Manganese toxicity is relatively visible at low concentrations. The Mn content allowed in the waters for sanitation hygiene is a maximum of 0.05 mg/l based on the Minister of Health of the Republic of Indonesia No. 32 of 2017. Water originating from acid mining sources may contain dissolved Mn

with a concentration of  $\pm 1$  mg/l. At a rather high pH and aerobic conditions, insoluble Mn is formed such as  $MnO_2$ ,  $Mn_3O_4$  or  $MnCO_3$ , although the oxidation of  $Mn^{2+}$  is relatively slow.

d) Lead

The level of lead (Pb) in the waters from the test results obtained an average of 40.25  $\mu g/l$ . This amount is very low compared to the maximum limit set for sanitation hygiene needs. There is no point where the Pb content exceeds the maximum threshold.

Heavy metals in waters that are difficult to degrade will be absorbed in the body of organisms so that heavy metals such as Fe, Mn and Pb are classified as dangerous heavy metals and can enter the body through the respiratory and digestive tracts. Heavy metals can cause acute and chronic poisoning. Acute lead poisoning is characterized by a burning sensation in the mouth, the occurrence of irritation in the gastrointestinal tract accompanied by diarrhea and symptoms of chronic poisoning are characterized by nausea, anemia, pain around the stomach and can cause paralysis (9).

2) Water biology testing

Sampling of water to be tested for total coliform at 30 points spread over 5 villages in the Astambul District, the results can be seen in table 5 below.

**Table 5 The results of the inspection of the biological quality of clean water in Astambul District in 5 villages (Kelampian Tengah, Kelampayan Ulu, Lok Gabang, Sungai Alat and Kaliukan)**

No	Sample	Total Coliform (Maximum Level=50CFU/100ml)	
<b>Middle Kelampian Village</b>			
1	1 point	1600	it is not in accordance with
2	Point 2	1600	it is not in accordance with
3	3 point	1600	it is not in accordance with
4	4 point	1600	it is not in accordance with
5	5 point	1.6	in accordance
<b>Average</b>		<b>1280,32</b>	<b>it is not in accordance with</b>
<b>Lok Gabang Village</b>			
6	1 point	1600	it is not in accordance with
7	Point 2	1600	it is not in accordance with
8	3 point	1600	it is not in accordance with
9	4 point	1600	it is not in accordance with
10	5 point	1600	it is not in accordance with
11	6 point	1600	it is not in accordance with
<b>Average</b>		<b>1600</b>	<b>it is not in accordance with</b>
<b>Tool River Village</b>			
12	1 point	1600	it is not in accordance with
13	Point 2	1600	it is not in accordance with
14	3 point	1600	it is not in accordance with
15	4 point	1600	it is not in accordance with

No	Sample	Total Coliform (Maximum Level=50CFU/100ml)	
16	5 point	1600	it is not in accordance with
17	6 point	1600	it is not in accordance with
18	7 point	1600	it is not in accordance with
<b>Average</b>		<b>1600</b>	<b>it is not in accordance with</b>
Kaliukan Village			
19	1 point	1600	it is not in accordance with
20	Point 2	1600	it is not in accordance with
21	3 point	1600	it is not in accordance with
22	4 point	1600	it is not in accordance with
23	5 point	1600	it is not in accordance with
24	6 point	1600	it is not in accordance with
<b>Average</b>		<b>1600</b>	<b>it is not in accordance with</b>
Ulu Kelampayan Village			
25	1 point	1600	it is not in accordance with
26	Point 2	1600	it is not in accordance with
27	3 point	1600	it is not in accordance with
28	4 point	1600	it is not in accordance with
29	5 point	1600	it is not in accordance with
30	6 point	350	it is not in accordance with
<b>Average</b>		<b>1391.67</b>	<b>it is not in accordance with</b>
<b>Overall Biology Average</b>		<b>1494.4</b>	<b>it is not in accordance with</b>

Source: Primary Data 2022

The results of testing water samples for the number of coliforms per 100ml from all points obtained an average of 1494.4CFU/100ml, this exceeds the maximum limit required for water used for sanitation hygiene purposes, which is 50CFU/100ml. There is only 1 point (3.33%) which has a total coliform value below 50CFU/100ml.

One of the parameters that must be met and has a direct effect on health is microbiological parameters, where one of the indicators is total coliform. In drinking water, the total coliform allowed is very small (50CFU/100ml). If the total coliform content in drinking water exceeds the maximum threshold, then the water is unsafe/unfit for consumption. Unsafe drinking water can certainly have a negative impact on health, especially for vulnerable groups such as toddlers, people with low immunity, and the elderly. One of the health problems that can arise from consuming unsafe water is waterborne disease, where diarrhea is one of the diseases most often associated with improper water consumption (15).

Total coliform is a group of bacteria that includes aerobic and facultative anaerobic bacteria, which are gram-negative bacteria. Most of the total coliform bacteria are heterotrophic and can increase in number in water and soil. Total coliforms can also survive and multiply in water distribution systems, especially if conditions permit. The presence of total coliforms can come from human or animal feces and can also occur naturally in water. Total coliform is only an indicator used to indicate that there could be other microbes in the water, for

example pathogenic microbes such as Giardia, Cryptosporidium, E.coli, and others (Arsyina, 2019). Based on the regulations contained in the Regulation of the Minister of Health of the Republic of Indonesia No.

Total coliform in Astambul District is known to have a very high value. This is because the rivers there are still used as a place for local residents to defecate. This activity is very large which causes a large number of bacteria in a waters. The river is still used by residents for various kinds of daily activities, from bathing to consumption.

#### IV. CONCLUSION

The availability of clean water in Astambul District based on physical parameters is still feasible and according to standards, where the average measurement results for temperature, DO, TDS and turbidity are according to standards. Based on chemical parameters, water quality in Astambul District is not suitable for consumption and needs to be treated. The results obtained are that the pH and Manganese content are not in accordance with the regulations set by the government. Biological parameter testing obtained a high average total coliform value and the water is not fit for consumption. Astambul sub-district is mostly covered by agricultural land. In addition, there are many swampy areas so that many water hyacinth plants are found and the land area is overgrown with coconut trees. These three plants can be used to help provide clean water by making activated charcoal and absorbing harmful substances in the water. Sources of water in the form of wells without a dividing wall are one of the causes of the problem of the low quality of the water obtained.

#### REFERENCES

- [1] G Dukabain, O., Theodolfi, R., & Telan, AB (2019). Improvement of Clean Water Facilities and Community Empowerment of Water User Groups in Hamlet III, Oelnasi Village, Kupang Regency. Proceedings of the National Sanitation National Committee, 384-389.
- [2] Bnpb. 2015. South Kalimantan Disaster Risk Assessment 2016-2021
- [3] Rahman, A. 2017. The Use of Geographic Information Systems for Mapping of Flood Prone Levels in Banjar Regency, South Kalimantan Province', *Enviroscienceteae*. Doi: 10.20527/Es. V13i1.3506.
- [4] Farrasati, R., Pradiko, I., Rahutomo, S., Sutarta, ES, Santoso, H. and Hidayat, F., 2019. Soil C-organic in oil palm plantations of North Sumatra: status and relationship with some soil chemical properties . *Journal of Soil and Climate*, 43(2), pp.157-165.
- [5] Nangaro, RA, Zety, E. and Titah, T., 2021, January. Analysis of soil organic matter content in traditional gardens of Sereh Village, Talaud Islands Regency. In *COCOS* (Vol. 3, No. 1).
- [6] Harahap, FS, Kurniawan, D. and Susanti, R., 2021. Mapping of soil pH and c-organic status of rainfed lowland soil in Panai Tengah Subdistrict, Labuhanbatu Regency. *Agroscience: Journal of Agronomy Research*, 23(1), pp.37-42.
- [7] Bolly, YY and Apelabi, GO, 2022. Analysis of Organic Matter Content of Rice Field Soil as an Effort to Assess Soil Fertility in Magepanda Village, Magepanda District, Sikka Regency. *Agrica*, 15(1), pp.26-32.
- [8] Ali, K., Sofyan, A., Abd Rachman, I. and Hasan, ADA, 2022. Study of Permeability and Soil Water Content in Three Types of Land Use in Gambesi, Ternate City. *Cannarium*, 20(1).
- [9] Koniyo, Y., 2020. Analysis of Water Quality at Freshwater Fish Cultivation Locations in Central Suwawa District. *Journal of Technopreneur (JTech)*, 8(1), pp.52-58
- [10] Earnestly, F., 2018. Analysis of Temperature, pH and Iron Metal Content in Groundwater Sources at the University of Muhammadiyah Sumatra Barat (UMSB) Padang Campus. *Tower of Science*, 12(1).
- [11] Djoharam, V., Riani, E. and Yani, M., 2018. Analysis of water quality and load carrying capacity of the Pesanggrahan river pollution in the DKI Jakarta province. *Journal of Natural Resources and Environmental Management*, 8(1), pp.127-133.
- [12] Astuti, AD, 2014. Irrigation water quality in terms of DHL, TDS, pH parameters in the rice fields of Bulumanis Kidul Village, Margoyoso District. *Journal of Research and Development: Media Information Research, Development and Science and Technology*, 10(1), pp.35-42.
- [13] Rahmat Eko, S. and Rilia, I., 2018. River Water Quality in Tanipah Village (Peat Beach), South Kalimantan. *BioLink Journal of Environmental Biology, Industry, Health*, 5, pp.1-10.
- [14] Putra, AY and Mairizki, F., 2019. Analysis of Color, Acidity and Iron Levels in Groundwater, Kubu Babussalam District, Rokan Hilir, Riau. *Journal of Catalysts*, 4(1), pp.9-14.
- [15] Arsyina, L., Wispriyono, B., Ardiansyah, I. and Pratiwi, LD, 2019. Relationship of Drinking Water Sources with Total Coliform Content in Household Drinking Water. *Indonesian Journal of Public Health*, 14(2), pp.18-23.

#### AUTHORS

First Author – Husaini, Environmental Health, Department of Environmental Health, Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

Second Author – Anugrah Nur Rahmat, Environmental Health, Department of Environmental Health, Public Health Program, Faculty of Medicine, Lambung Mangkurat University

Third Author – M. Saidi Hidayat, Student of Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

Fourth Author – Taufik, Student of Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

Fifth Author – M. Gilmani, Student of Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

Correspondence Author – Husaini, Environmental Health, Department of Environmental Health, Public Health Program, Faculty of Medicine, University of Lambung Mangkurat

